



2010 SMOKE SPEC SHEET

by NEG as of 12/01/09

A/A: 33" +/- 3/16"
B.H.: 7-1/8" +/- 1/8"

String: 92-5/8"
Cable: 35-5/16"

MOD:	DRAW LENGTH²:	DRAW STOP POSITION:	IBO RATING¹:
HPS-#1	30.5"	7	324-319
HPS-#2 (30-HPS)	30"	6.5	319-314
HPS-#3 (29.5-HPS)	29.5"	6	314-309
HPS-#4 (29-HPS)	29"	5.5	309-304
HPS-#5 (28.5-HPS)	28.5"	5	304-299
HPS-#6 (28-HPS)	28"	4.5	299-294
HPS-#7 (27.5-HPS)	27.5"	4	294-289
HPS-#8 (27-HPS)	27"	3	289-284
HPS-#9 (26.5-HPS)	26.5"	2	283-278
HPS-#10 (26-HPS)	26"	1	278-273

Limb Deflections:	Limb Weights:	Limb Lengths:
68-76	50-53	13-1/2"
84-92	60-63	13-1/2"
104-112 (D)	70-73	13-1/2"

Cam System: HPS Cam
Let-Off: 80%
Speed Studs: 30gr. @ 2" from tip of cam.
Spacers: .030" on cable side- White Teflon
I-Glide Rod: 7.00" (No Grooves)
Suppressor Rod: 7.15" (2 Grooves) set @ 1/16" from string
Bearings: Flanged - P/N:12216
Pivots: 0.162"

Notes:

- 1.) Measured with 350-grain arrow @ 70#.
- 2.) Plus 3/8", Minus Nothing