



2013 BLISS SPEC SHEET

by SP as of 7/16/13

A/A: 31" +/- 3/16"

String: 86 3/8"

B.H.: 7 +/- 1/8"

Cable: 33 3/8"

| MOD POS | DRAW LENGTH ² | | IBO RATING ¹ : |
|---------|--------------------------|------|---------------------------|
| | A | B | |
| 1 | | 27.5 | 295-290 |
| 2 | 27 | | 290-285 |
| 3 | | 26.5 | 285-280 |
| 4 | 26 | | 280-275 |
| 5 | | 25.5 | 275-270 |
| 6 | 25 | | 270-265 |
| 7 | | 24.5 | 265-260 |
| 8 | 24 | | 260-255 |
| 9 | | 23.5 | 255-250 |
| 10 | 23 | | 250-245 |

| Limb Deflections: | Limb Weights: | Limb Lengths: |
|-------------------|---------------|------------------|
| 75-79 | 45-47 | 13" Solid Pinned |
| 108-112 | 60-63 | 13" Solid Pinned |

Cam System:

Fluid SD Cam

Let-Off:

65-75%

Spacers:

Cam- .050" cable side- black

Idler- .110" cable side- black

Speed Studs:

(none)

Cable Guard:

7.75" Carbon Rod w/ Black Slide

Suppressor Rod:

6.5937" (3 groove) set @ 1/16" from string

Bearings:

Flanged - P/N:12216

Pivots:

0.162" (Blue)

Notes:

1.) Measured with 200 grain arrow @ 40#.

2.) "A" mod covers 1" draw lengths. "B" mod covers 1/2" draw lengths. Plus 1/4" minus nothing.