

Quest 2015 Forge Specification Sheet

Technical Specifications

Axle to Axle;	31.125" (+/- 1/8")	Cable Guard Rod Length;	7.75"
Timing;	See Pic#1	Top Idler Spacers;	.185" (+/- .005" to fit)
Limb Deflection:	#95	Bottom Cam Spacers;	.200" on cable side/.085"on string side
Brace Height;	7"	String Stop Assembly;	W-000508
Let-off;	80-73% per setting below	Limb Rocker;	R-000027(blue)

Cam System

Fluid Cam (draw lengths are minus nothing, plus 1/4")

Mod Position	Draw Stop Position	Draw Length	ATA RATING
#1	2.5	30"	315-310
#2	3	29.5"	310-305
#3	4	29"	305-300
#4	5	28.5"	300-295
#5	5.5	28"	295-290
#6	6.5	27.5"	290-285
#7	7	27"	285-280
#8	8	26.5"	280-275
#9	9	26"	275-270
#10	9.5	25.5"	270-265

String Specifications

Serving Locations									Overall Length
String	17 3/8"	23 1/4"	25 1/4"	28"	32"	43"	61 7/8"	80"	87 7/8"
Cable	2"	25"	-	-	-	-	-	-	33 1/2"



PIC #1