



## 2011 HAMMER SPEC SHEET

by NEG as of 4/26/11

**A/A:** 33" +/- 3/16"

**String:** 91-11/16"

**B.H.:** 7-1/8" +/- 1/8"

**Cable:** 34-3/4"

<b>MOD:</b>	<b>DRAW LENGTH<sup>2</sup>:</b>	<b>IBO RATING<sup>1</sup>:</b>
CR9	30"	315-310
CR8	29.5"	310-305
CR7	29"	305-300
CR6	28.5"	300-295
CR5	28"	295-290
CR4	27.5"	290-285
CR3	27"	285-280
CR2	27.5"	280-275
CR1	27"	275-270

<b>Limb Deflections:</b>	<b>Limb Weights:</b>	<b>Limb Lengths:</b>
75-79	50-53	13-1/2"
93-98	60-63	13-1/2"
108-118 (D)	70-73	13-1/2"

**Cam System:** QS Cam  
**Let-Off:** 80%  
**Spacers:** .030" on cable side- White Teflon  
**Cable Guard:** 7.750" rod w/ white Teflon slide  
**Suppressor Rod:** 6.967" (2 groove) set @ 1/16" from string  
**Bearings:** Flanged - P/N:12216  
**Pivots:** 0.162"

Notes:

- 1.) Measured with 350-grain arrow @ 70#.
- 2.) Minus nothing, plus 3/8"