



2010 HEAT SPEC SHEET

by NEG as of 9/15/09

A/A: 33-1/8" +/- 3/16"

String: 93"

B.H.: 6-5/8" +/- 1/8"

Cable: 35-7/16"

MOD:	DRAW LENGTH:	DRAW STOP POSITION:	IBO RATING ¹ :
HPS-#1	30"	6.5	330-325
HPS-#2 (30-HPS)	29.5"	6	325-320
HPS-#3 (29.5-HPS)	29"	5.5	320-315
HPS-#4 (29-HPS)	28.5"	5	315-310
HPS-#5 (28.5-HPS)	28"	4.5	310-305
HPS-#6 (28-HPS)	27.5"	4	305-300
HPS-#7 (27.5-HPS)	27"	3	300-295
HPS-#8 (27-HPS)	26.5"	2	295-290
HPS-#9 (26.5-HPS)	26"	1.5	290-285
HPS-#10 (26-HPS)	25.5"	1	285-280

Limb Deflections ⁶ :	Limb Weights:	Limb Lengths:
	50-53	13"
	60-63	13"
	70-73	13"

Cam System: HPS Cam
Let-Off: 80%
Speed Studs: 30gr. @ 2" from tip of cam.
Spacers: .030" on cable side- White Teflon
I-Glide Rod: 6.50" (3 Grooves)
Suppressor Rod: 6.65" (3 Grooves) set @ 1/16" from string
Bearings: Flanged - P/N:12216
Pivots: 0.162"

Notes:

- 1.) Measured with 350-grain arrow @ 70#.
- 2.) Deflection machine set to these settings. X: 3.125", Y: 6.251", Stroke: 3.125"