



2011 PRIMAL SPEC SHEET

by NEG as of 4/26/11

A/A: 32-1/8" +/- 3/16"

String: 56"

B.H.: 7" +/- 1/8"

Cable: 36-11/16"

MODS¹:	DRAW LENGTH²:	IBO RATING³:
SYNC-#1	30"	330-325
SYNC-#2	29.5"	325-320
SYNC-#3	29"	320-315
SYNC-#4	28.5"	315-310
SYNC-#5	28"	310-305
SYNC-#6	27.5"	305-300
SYNC-#7	27"	300-295
SYNC-#8	26.5"	295-290

Limb Deflections:	Limb Weights:	Limb Lengths:
70-74	50-53	13"-Solid Pinned
89-92	60-63	13"-Solid Pinned
104-110	70-73	13"-Solid Pinned

Cam System: SYNC Cam System
Let-Off: 80%
Speed Studs: 30gr. @ 2" from tip of each cam.
Spacers: .045" on cable side
Cable Guard: Carbon Steel flex guard- P/N: 14503
Suppressor Rod: 6.9"(4 groove) set @ 1/16" from string
Bearings: Flanged - P/N:12216
Pivots: 0.162"(Blue)

Notes:

- 1.) Cam designation "A" goes on top of R.H. model, where "B" goes on top for L.H. model.
- 2.) Minus nothing, plus 1/4"
- 3.) Measured with 350-grain arrow @ 70#.