



2012 ROGUE SPEC SHEET

by SP as of 11/15/11

A/A: 31" +/- 3/16"

String: 87-7/8"

B.H.: 7-1/2" +/- 1/8"

Cable: 33-1/2"

MOD POS	DRAW LENGTH ² :	IBO RATING ¹ :
1	30.5"	320-315
2	30"	315-310
3	29.5"	310-305
4	29"	305-300
5	28.5"	300-295
6	28"	295-290
7	27.5"	290-285
8	27"	285-280
9	26.5"	280-275
10	26"	275-270

Limb Deflections:	Limb Weights:	Limb Lengths:
75-79	50-53	13-1/2"
93-98	60-63	13-1/2"
115-118	70-73	13-1/2"

Cam System:

Fluid Rotating Mod Cam

Let-Off:

80%

Spacers:

Cam- .060" both sides- black

Idler- .050" both sides- black

Speed Studs:

(none)

Cable Guard:

7.75" Carbon Rod w/ Black Slide

Suppressor Rod:

6.967" (2 groove) set @ 1/16" from string

Bearings:

Flanged - P/N:12216

Pivots:

0.162"

Notes:

- 1.) Measured with 350-grain arrow @ 70#.
- 2.) Minus nothing, plus 1/4"