



## 2012 TORRENT SPEC SHEET

by SP as of 11/16/11

**A/A:** 31" +/- 3/16"

**String:** 87-7/8"

**B.H.:** 7" +/- 1/8"

**Cable:** 33-1/2"

MOD POS	DRAW LENGTH <sup>2</sup> :	IBO RATING <sup>1</sup> :
1	30"	319-314
2	29.5"	314-309
3	29"	309-304
4	28.5"	304-299
5	28"	299-294
6	27.5"	294-289
7	27"	289-284
8	26.5"	283-278
9	26"	278-273
10	25.5"	273-268

Limb Deflections:	Limb Weights:	Limb Lengths:
70-74	50-53	13"-Solid Pinned
89-92	60-63	13"-Solid Pinned
104-110	70-73	13"-Solid Pinned

**Cam System:**

Fluid Rotating Mod Cam

**Let-Off:**

80%

**Spacers:**

Cam- .050" string side- black

.020" cable side- black

Idler- .035" both sides- black

**Speed Studs:**

30 grn. @ 2 3/8" from tip of cam

**Cable Guard:**

I-Glide (4 groove)

**Suppressor Rod:**

6.5937" (3 groove) set @ 1/16" from string

**Bearings:**

Flanged - P/N:12216

**Pivots:**

0.162"

Notes:

- 1.) Measured with 350-grain arrow @ 70#.
- 2.) Minus nothing, plus 1/4"